

Count on Bergstrom

Right parts. Right price. Right on time.



Introducing the KK-600 Kombo



KK-600 Kombo



Features

- High performance wall mount AC/heater
- Heavy duty steel construction
- 3-speed blower switch
- Adjustable thermostat and water valve controls
- Durable double wheel plastic blower
- (3) 3" Directional top louvers
- (4) Directional front louvers
- Easy access refrigerant and heater hose connections for improved serviceability
- Available in 12 or 24 voltages

Weights & Dimensions

- Weight 70 lbs
31.8 kg
- Width (Case) 18.9 in
480 mm
- Width (Overall) 21 in
533 mm
- Height (Case) 26.5 in
674 mm
- Height (Overall) 32 in
813 mm
- Depth 9 in
229 mm



Technical Specifications

- Performance
 - Cooling** 90 °F (32.2 °C)DB @ 70% RH
33,320 BTU/h
9.8 kW
 - Heating** SAE J638 @ 18.2 LPM (4.8 GPM)
47,750 BTU/h
14.0 kW
- Air Flow
 - Cooling** 325 SCFM
552 SCMh
 - Heating** 375 SCFM
637 SCMh
- Current Draw 12 Amps @ 13.8VDC
6 Amps @ 27.6VDC

Warranty

- 1 year limited warranty on parts and labor

Applications

- Over-the-Road Vehicles
- Industrial Vehicles
- Agricultural Equipment
- Light Duty Off-Highway Equipment
- Mining Vehicles
- Delivery Vans
- Money Haulers

